



Malla Ondulada.

Abertura 20 mm x 20 mm					
Alt.	Calibre				
	14	12.5	10.5	8	6
1	x	x	x		
1.25	x	x	x		
1.5	x	x	x		
2	x	x	x		
Abertura 25 mm x 25mm					
Alt.	Calibre				
	14	12.5	10.5	8	6
1		x	x		
1.25		x	x		
1.5		x	x		
2		x	x		
Abertura 30 mm x 30mm					
Alt.	Calibre				
	14	12.5	10.5	8	6
1	x	x	x	x	
1.25	x	x	x	x	
1.5	x	x	x	x	
2	x	x	x	x	
Abertura 40 mm x 40mm					
Alt.	Calibre				
	14	12.5	10.5	8	6
1		x	x	x	x
1.25		x	x	x	x
1.5		x	x	x	x
2		x	x	x	x
Abertura 50 mm x 50mm					
Alt.	Calibre				
	14	12.5	10.5	8	6
1			x	x	x
1.25			x	x	x
1.5			x	x	x
2			x	x	x

Especificaciones

Fabricación en rollos de 10 M.L.

Utilizamos alambres galvanizados por inmersión en caliente.

Utilizamos P.V.C de alta calidad resistente a la acción del sol.

Se fabrican, aberturas, alturas longitudes diferentes a los estándares.